## Declaration of Performance (DoP)



No. F163-CPR-20130821 (Revision 1)	
Product Type:	Roomheaters fired by solid fuel
Type, batch or serial number: [Article 11-4]	Jøtul F 160 Series
	(Jøtul F 163, Jøtul F 165, Jøtul F 167)
Intended use of the product:	Roomheater burning solid fuel without water supply
Name and Address of the manufacturer:	Jøtul AS
[ Article 11-5]	Postboks 1411, 1602 Fredrikstad, Norway
	Tel.: +47 69 35 90 00
	E-mail: post@jotul.no
Contact address: [Article 12-2]	No relevance
AVCP:	System 3
System(s) of assessment and verification of constancy op performance (AVCP) of the construction product as set out in CPR, Annex V	
Notified body:	RWE Power AG, Feuerstättenprüfstelle
	NB-No 1427
Test report no:	FSPS-Wa 1964-EN, FSPS-Wa 2009-EN, FSPS-Wa 2154-EN
Declared performance:	
Harmonized technical specification	EN 13240:2001/A2:2004/AC:2007
Essential characteristics	Performance
Fire safety	-
Reaction to fire	A1
	AI
Distance to combustible materials	Minimum distances, in mm
	F 163, F 165, F 167
	Rear = 200
	Sides = 700
	Corner = 500
	Front = 1000
Risk of burning fuel falling out	No
Emission of combustion products	CO [0,099 %]
Emission of compassion products	NOx [120 mg/m3]
	OGC [107 mgC/m3]
	Dust [20 mg/m3]
Surface temperature	Pass
Electrical safety	-
Cleanability	Pass
Maximum water operating pressure	- T[200°C]
Flue gas temperature at nominal heat output	T [200°C]
Mechanical resistance (to carry a chimney/flue)	NPD
Thermal output	
Normal heat output	5 kW
Room heating output	- kW
Water heating output	-*kW
Energy efficiency	η [82%]

The performance of the product identified in points 1 and 2 in conformity with the declared performance in point 8.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed on behalf of the manufacturer:

Anna Øren

R&D Manager

(Name and function)

Fredrikstad, 26.06.2018

(Place and date of issue)

(Signature)